Article Specification



PB-10 Basic Bench Top pH Meter

- Automatic calibration with recognition of up to 16 buffers
- Automatic temperature compensation
- Electrode check during calibration
- Stability icon
- BNC connector for glass-membrane pH electrodes or Redox electrodes

Th. ///	•	
VIA	suring	range
TATCH	Suring	range

Voltage: $\pm 1500.0 \text{ mV}$ pH: 0 to + 14.00 Temperature: $-5 \text{ to} + 105^{\circ}\text{C}$

Resolution

 $\begin{array}{ll} \mbox{Voltage:} & \pm \ 0.1 \ \mbox{mV} \\ \mbox{pH:} & \pm \ 0.01 \\ \mbox{Temperature:} & \pm \ 0.1 \ \mbox{C} \end{array}$

Accuracy

 $\begin{array}{ll} \mbox{Voltage:} & \pm \ 0.4 \ \mbox{mV} \\ \mbox{pH:} & \pm \ 0.01 \\ \mbox{Temperature:} & \pm \ 0.2 \mbox{°C} \end{array}$

Operation Easy with four keys:

- pH/mV
- Standardize
- Setup
- Enter

Dimensions (W x D x H) 230x120x80 mm

Net weight approx. 2 kg

- Standard Equipment/Equipment Supplied:
- Electrode holding arm and base plate.
- pH combination Gel-filling electrode
- With integrated temperature sensor (3-in-1)
- AC adapter



