

pH55 PRO/pH56 PRO

Compact, pocketable, waterproof pH/Temperature testers with replaceable electrode

Water-resistant pH testers with large dual-level LCD that displays pH and temperature (°C or °F). The large display shows readings in an extended range from -2.0 to 16.0 pH (**pH56** has a 0.01 pH resolution) and simultaneously shows temperature from -5.0 to 60.0°C or 23.0 to 140.0°F. They have a stability indicator and hold function that freezes the display for easy and accurate recording. The large display also has graphic symbols to guide you through all operations.

Complete with a temperature probe for fast and more precise temperature measurement they compensate automatically for temperature. Calibration is made automatically in 1 or 2 points with memorized standard and NIST buffer sets. Auto power OFF saves battery power after non-use.

The double-junction electrode can be replaced in a very fast and simple way! The modular design allows easy electrode and battery replacement.

Specifications	pH55 PRO	pH56 PRO
		
Range	pH Temp. -2.0 to 16.0 pH -5.0 to 60.0°C / 23.0 to 140.0°F	pH Temp. -2.00 to 16.00 pH -5.0 to 60.0°C / 23.0 to 140.0°F
Resolution	pH Temp. 0.1 pH 0.1°C / 0.1°F	pH Temp. 0.01 pH 0.1°C / 0.1°F
Accuracy (@25°C)	pH Temp. ±0.1 pH ±0.5°C / ±1°F	pH Temp. ±0.05 pH ±0.5°C / ±1°F
Typical EMC Deviation	pH Temp. ±0.1 pH ±0.3°C / ±0.6°F	pH Temp. ±0.02 pH ±0.3°C / ±0.6°F
Calibration	automatic, 1 or 2 points with 2 sets of memorized buffers (pH 4.01, 7.01, 10.01 or 4.01, 6.86, 9.18)	automatic, 1 or 2 points with 2 sets of memorized buffers (pH 4.01, 7.01, 10.01 or 4.01, 6.86, 9.18)
Temperature Compensation	automatic from -5 to 60°C	automatic from -5 to 60°C
Probe	Mi56P (replaceable)	Mi56P (replaceable)
Environment	-5 to 50°C / 32 to 122°F; max RH 100%	-5 to 50°C / 32 to 122°F; max RH 100%
Battery Type	4 x 1.5V; IEC LR44, A76 (included)	4 x 1.5V; IEC LR44, A76 (included)
Battery Life	approx. 300 hours of use	approx. 300 hours of use
Auto-off	after 8 minutes of non-use	after 8 minutes of non-use
Packaging dimensions	254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight	200 g	200 g

Accessories

Mi56P	Replaceable electrode for pH55 & pH56	M10010B	pH 10.01 buffer solution 20 mL sachet (25 pcs)
M10000B	Electrode rinse solution, 20 mL sachet (25 pcs)	MA9004	pH 4.01 buffer, 230 mL bottle
M10004B	pH 4.01 buffer solution 20 mL sachet (25 pcs)	MA9007	pH 7.01 buffer solution, 230 mL bottle
M10007B	pH 7.01 buffer solution 20 mL sachet (25 pcs)	MA9010	pH 10.01 buffer solution, 230 mL bottle
		MA9015	Electrode storage solution, 230 mL
		MA9016	Electrode cleaning solution, 230 mL
		MA753	Hard carrying case for 2 testers

Ordering Information

pH55 PRO and **pH56 PRO** is supplied complete in a carton box with protective cap, 20 mL pH 4.01 and pH 7.01 sachets of calibration solution.

Optionally **pH55 PRO** is also available in a kit (**Mi5559** or **Mi5560**) together with **EC59 PRO** or **EC60 PRO** EC/TDS/Temp Meters.



pH/Temperature Sensor

The **pH55 PRO** and **pH56 PRO**'s exposed temperature sensor provides fast response time, and its proximity to the pH electrode guarantees much more accurate temperature compensated readings.



Replaceable electrode

Replace the electrode in a fast and simple way yourself! Just unscrew the plastic ring on the top of the electrode and replace the electrode with a new one.

