

## 10 μL Gastight Syringe Model 1701 RN, Small Removable Needle, Needle Sold Separately

Specification Sheet (Part/REF # 7653-01)



The 1700 series syringes are the gas tight version of the original 700 series syringes. This series of gas tight syringes is ideal for dispensing volumes from 1  $\mu$ L up to 500  $\mu$ L. A variety of different terminations and needle options are available in this series.

## **Product Specifications**

Volume	10 μL
Syringe Type	Gastight
Syringe Series	1700
Termination	Removable Needle (RN)
Needle	Small RN
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	Yes
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	115°C / 239°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.018 inches (0.460 mm)



US: +1-800-648-5950 EU: +40-356-635-055



Specifications are subject to change without notice <a href="https://www.hamiltoncompany.com/laboratory-production">https://www.hamiltoncompany.com/laboratory-production</a>	lucts/syringes/7653-01	Spec. Version B
Sales Quantity	1 syringe per pack	
Std Needle Dead Volume	N/A	
Barrel Outer Diameter	0.260 inches (6.60 mm)	

HAMILT®N°

US: +1-800-648-5950 EU: +40-356-635-055